

# Philips Silicone Coated Lamps

Silicone Coating; ideal for standard, industrial rough surface, appliance and sign use



## ▶ Special Silicone Coating

Resists breakage

## ▶ Absorbs Impact

## ▶ Resists Breakage

Or shattering if bulb is hit or dropped

## ▶ Resists Moisture

## ▶ Repels Machine Splatter

Without breakage caused by thermal shock

***Ideal for factory lighting, new construction, food serving areas, refrigerators, garden fountains and drop cords***



# PHILIPS

**Philips Lighting Company**  
**200 Franklin Square Drive**  
**P.O. Box 6800**  
**Somerset, NJ 08875-6800**  
**1-800-555-0050**

[www.philips.com](http://www.philips.com)

**Philips Lighting**  
**281 Hillmount Road**  
**Markham, Ontario**  
**Canada L6C 2S3**  
**1-800-555-0050**

A Division of Philips Electronics North America Corporation

A Division of Philips Electronics Ltd.

Printed in USA 7/05

P-2544-C

## Philips Silicone Coated Lamps

Electrical, Technical and Ordering Data (Subject to change without notice)

Product Number	Ordering Code	Watts	Volts	Pkg. Qty.	Description	Bulb Type	Base	Rated Avg. Life (Hrs.) <sup>1</sup>	MOL (In.)	Class, Filament
<b>General Lighting</b>										
30031-9	25A/TF	25	120	120	Frost Silicone Coated	A-19	Medium	2500	3 <sup>1</sup> / <sub>16</sub>	B, C-9
30033-5	40A/TF	40	120	120	Frost Silicone Coated	A-19	Medium	1500	4 <sup>1</sup> / <sub>16</sub>	C, CC-6
30038-4	60A/TF	60	120	120	Frost Silicone Coated	A-19	Medium	1000	4 <sup>1</sup> / <sub>16</sub>	C, CC-6
30051-7	100A21/TF	100	120	120	Frost Silicone Coated	A-21	Medium	750	5 <sup>1</sup> / <sub>16</sub>	C, CC-8
30056-6	150PS25/TF	150	120	60	Frost Silicone Coated	PS-25	Medium	1000	6 <sup>1</sup> / <sub>16</sub>	C, C-9
14298-3	200/TF	200	120	60	Frost Silicone Coated	PS-30	Medium	750	8 <sup>1</sup> / <sub>16</sub>	C, C-9
<b>Industrial Service Lamps</b>										
25836-8*	60A/35/TF	60	120	60	Frost Silicone Coated Industrial Service	A-19	Medium	3500	4 <sup>1</sup> / <sub>16</sub>	C, C-9
25838-4†	100A21/35/TF	100	120	60	Frost Silicone Coated Industrial Service	A-21	Medium	3500	5 <sup>1</sup> / <sub>16</sub>	C, C-9
22965-8†	150A/25/35/TF	150	120	60	Frost Silicone Coated Industrial Service	A-25	Medium	3500	6 <sup>1</sup> / <sub>16</sub>	C, C-9
14300-8†	200/35/TF	200	120	60	Frost Silicone Coated Industrial Service	PS-30	Medium	3500	8 <sup>1</sup> / <sub>16</sub>	C, C-9
<b>Rough Service Lamps</b>										
30034-3	50A/RS/TF	50	120	120	Frost Rough Service Silicone Coated	A-19	Medium	1000	3 <sup>1</sup> / <sub>16</sub>	B, RC-9
20922-1	75A/RH/TF 21/1	75	120	12	Frost Silicone Coated Tough Bulb	A-21	Medium	1000	5 <sup>1</sup> / <sub>16</sub>	C, RC-9
14305-7	200PS30/RS/TF	200	120	60	Frost Rough Service Silicone Coated	PS-30	Medium	1000	8 <sup>1</sup> / <sub>16</sub>	C, C-9
<b>Appliance Lamps</b>										
25109-0	40A15/TF	40	120	120	Refrigerator	A-15	Medium	1000	3 <sup>1</sup> / <sub>2</sub>	C, C-9
<b>Reflector Sign Lamp</b>										
22601-9	30R20/SFL/TF	30	130	120	Reflector Sign	R-20	Medium	6000	3 <sup>1</sup> / <sub>16</sub>	C, C-9

1) Rated average life is the length of operation (in hours) at which point an average of 50% of the lamps will still be operational and 50% will not.

\* Silicone Coating reduces lumen output from Standard Values from 3%–5% for all types.

† Operate base up.

